

PLANK CHALET 20 mm tongue/ groove

Technical information:

Produced according to:	European parquet norm EN 13489 - 2002
Dimension:	20 x 200/ 250/ 300/ 350/ 395 x 2200 mm
Toplayer:	about 4.5 mm
Construction:	3-layer construction; Hardwood toplayer, middlelayer and bottomlayer made of spruce Toplayer about 4.5 mm Middlelayer 10.5 mm Bottomlayer 5 mm
Boards / m² per carton:	-
Cartons/ m² per pallet:	-
Slotted top layers per carton/ minimum length (mm):	-
Weight per carton/ pallet in kg:	-
Floor heating systems:	Well suitable
Fire behavior ¹⁾:	Cfl-s1 and Dfl-s1 depending on wood specie and surface treatment
Content of formaldehyd ²⁾:	E1
Content of pentachlorphenol (PCP) ²⁾:	not detectable
Density kg/ m³ ²⁾:	about 600
Antislip performance:	Live Natural USRV 40 ²⁾
Abrasion resistance:	-
Thermal conductivity ²⁾:	0.15 W/ mK
Areal thermal resistance ⁵⁾:	0.133 m ² K/ W



DOP 4658-1.1-07.2013



Emissionsgeprüftes Bauprodukt nach DIBT-Grundsätzen.

¹⁾ according to DIN EN 13501-1, ²⁾ according to DIN 14342, ³⁾ according to ENV 13696, ⁴⁾ according to DIN 68861, ⁵⁾ according to EN 12524