

Ultimate Oak



Product informatie Product information Information produit Produkt Daten

	Level	●●● SUPER
Europese classificatie • European classification Classification européenne • Europäische Klassifizierung	EN ISO 10874	23 - 31
Totale dikte • Total thickness Épaisseur totale • Gesamtdicke	EN ISO 24346	ca. 3,00 mm
Slijtlaag • Wearlayer Couche d'usure • Nutzschiicht	EN ISO 24340	ca. 0,30 mm
Behandeling slijtlaag • Wear layer treatment Traitement couche d'usure • Schutz vor Schmutz		PU / Natural feel
Totaal gewicht • Total weight Poids total • Gewicht	EN ISO 23997	ca. 2200 g/m ²

Formaat & verpakking Size & packing Dimensions & emballage Abmessung & Verpackung

Breedte • Width Largeur • Breite	2 m	(3 m)	4 m
Standaard lengte • Standard length Longeur standard • Standardlänge	ca. 30 m	(ca. 30 m)	ca. 30 m
Standaard rolgewicht • Weight of standard roll Poids standard des rouleaux • Standard-Rollengewicht	ca. 136 kg	(ca. 204 kg)	ca. 272 kg

Technische informatie Technical information Information technique Technische Daten

Antislip • Slip resistance Glissance • Rutschfest	DIN 51130	DS
Slipweerstand • Sliprestraint Résistance au glissement • Rutschemmung		R11
Formaldehydeklasse • Formaldehyde group Classe formaldéhyde • Formaldehyde Klassifizierung	ENV 717-1	E1
Brandklasse • Inflammability Classement feu • Brandverhalten	EN 13501	Bfl-S1
Contactgeluidsisolatie • Acoustical insulation Isolation acoustique • Trittschallverbesserungsmaß	ISO 717	17 dB
Vloerverwarming • Underfloor heating Chauffage par le sol • Fußbodenheizung	EN 12524	Geschikt • Suitable Adapté • Geeignet
Thermische geleidbaarheid • Thermal conductivity Conductivité thermique • Wärmeleitfähigkeit	EN 12524	0,25 W / mK
Warmteweerstand • Thermal resistance Résistance thermique • Wärmedurchlasswiderstand	EN ISO 12466	0,0120 m ² K/W
Bestendigheid tegen huishoudelijke chemicaliën • Resistance to household chemicals Résistance aux produits d'entretien domestiques • Haushaltschemikalienbeständigkeit	EN ISO 26987	Zeer goed • Very good Très bon • Sehr gut
TOG Values	ISO 5085-1	0.21
Garantie • Warranty Garantie • Garantie		15 jaar • 15 years 15 ans • 15 Jahr

IVC biedt u garantie tegen fabrieksfouten en vroegtijdige slijtage bij normaal residentieel gebruik. • The warranty covers manufacturing defects and early wear due to normal residential use.
La garantie couvre les erreurs de fabrication et l'usure précoce lors d'un emploi normal résidentiel. • Die Garantie gewährleistet Fabrikationsfehler und frühzeitiges Abnutzen in normalen Wohnbereich

CE EN 14041 : 2004
06
07/04/2014
DOP_V190



a brand of **ivc** group
IVC group | Nijverheidslaan 29 | B-8580 Avelgem | Belgium
T +32 (0)56 65 32 11 | F +32 (0)56 65 32 29
info@ivcgroup.com | www.ivcgroup.com