

# CENTAUR



Guarantee

Garantie

Garantie

Garantie










## Residential use only

## Commercial use only

	Product information Produkt informatie	Produkt Daten Information produit		
	Total thickness Totale dikte	Gesamtstärke Epaisseur totale	EN 428	2,25 mm
	Wearlayer Slijtlaag	Nutzschicht Couche d'usure	EN 429	0,60 mm
	Width Breedte	Breite Largeur	EN 426	2m 3m 4m
	Standard length Standard rollengte	Standard Rollenlänge Longueur standard	EN 426	30m
	Total roll weight Totaal rolgewicht	Total Rollengewicht Poids total des rouleaux	EN 430	2330 g/m <sup>2</sup>
	Classification Classificatie	Klassifizierung Classification	EN 685	23
				33
				42

	Technical information Technische informatie	Technische Daten Information technique		
	Light stability Lichtechtheid	Lichtechtheit Résistance à la lumière	ISO 105-B02	≥ 6
	Dimensional stability Dimensionele stabiliteit	Dimensionsstabilität Stabilité dimensionnelle	EN 434	≤ 0,40%

<b>CENTAUR</b>				
	Impact sound improvement Contactgeluidsisolatie	Trittschallschutz Isolation acoustique	EN ISO 717/2	ΔLw 10dB
	Underfloor heating Vloerverwarming	Fussbodenheizung Chauffage par le sol	EN 12667	Suitable Geschikt Geeignet Convenable
	Residual indentation Restindrukking	Eindruckverhalten Poinçonnement	EN 433	always ≤ 0,20 mm; general ≤ 0,1 mm
	Reaction to fire Brandklasse	Brandverhalten Indice d'incendie	EN 13501-1	B <sub>fl</sub> S1
	Slipresistance Slipweerstand	Rutschhemmung Glissance	EN 13893	DS
	Castor chair Rolstoel	Rolstuhl Chaise à roulette	EN 425	Suitable Geschikt Geeignet Convenable


B.I.G. Floorcoverings Rijksweg 442 8710 - Wielsbeke
<b>06</b>
<b>EN 14041:2004</b> Expanded (cushioned) polyvinyl chloride floor coverings (EN653)
<b>Reaction to fire:</b> Class Bfl/s1
<b>Slipperiness:</b> DS
<b>Formaldehyde:</b> E1
EN 653

 
B.I.G. Floorcoverings Rijksweg 442 8710 - Wielsbeke
U3 P3 E2 C2
n° du certificat: 344-002.1